

## SECTION 122113 - HORIZONTAL LOUVER BLINDS

## PART 1 - GENERAL

## 1.1 SECTION REQUIREMENTS

- A. Salvage, clean, protect, and reinstall existing horizontal blinds.
- B. Provide units to match existing at locations with missing or damaged units

## PART 2 - PRODUCTS

## 2.1 HORIZONTAL LOUVER BLINDS

- A. Manufacturers:
  - 1. Hunter Douglas.
  - 2. Inside Outfitters
  - 3. Kirsch.
- B. Provide blinds passing flame-resistance testing according to NFPA 701.
- C. Louver Slats: Aluminum, antistatic polyester coated.
- D. Slat Width: 1 inch.
- E. Headrail: Formed steel or extruded aluminum; long edges returned or rolled; fully enclosing operating mechanisms on three sides and ends.
- F. Tilt Operation: Manual with wand.
- G. Valance: Manufacturer's standard.
- H. Mounting: To Match Existing.
- I. Colors, Textures, Patterns, and Gloss: As selected from manufacturer's full range, to match existing.
- J. Fabrication: Comply with AWCMA Document 1029 unless otherwise indicated.
  - 1. Fabricate concealed components from noncorrodible or corrosion-resistant-coated materials.
  - 2. Provide lifting and tilting mechanisms with permanently lubricated moving parts.

## PART 3 - EXECUTION

## 3.1 INSTALLATION

- A. Install blinds level, plumb, and located not closer than 1 inch to interior face of glass.
  - 1. Mount units in relation to head and jamb to match existing units.

END OF SECTION 122113

## SECTION 124813 - ENTRANCE FLOOR MATS AND FRAMES

## PART 1 - GENERAL

## 1.1 SECTION REQUIREMENTS

- A. Submittals: Product Data and Samples.

## PART 2 - PRODUCTS

## 2.1 FLOOR MATS AND FRAMES

- A. Basis of Design: The design is based on Balco, Entrance Matting System, Pebblestone. Comparable products, as determined by Architect, by one of the following manufacturers may be provided:
  - 1. C/S Group.
  - 2. Pawling.
- B. Carpet-Type Mats: Polypropylene carpet bonded to flexible vinyl backing to form mats 3/8 or 7/16 inch thick with nonraveling edges.
  - 1. Color: As selected by the Architect from Manufacturer's standard line.
  - 2. Pattern: As selected by the Architect from Manufacturer's standard line.
- C. Mat Frame: Tapered, flexible, vinyl edges; size and style to fit floor mat.
  - 1. Color: As selected by the Architect from Manufacturer's standard line.

## PART 3 - EXECUTION

## 3.1 INSTALLATION

- A. Coordinate elevation of tops of mat surfaces with bottom of doors that swing across mats to provide adequate clearance.
- B. Install surface-type units as indicated.

END OF SECTION 124813